SNAS slovenská národná akreditačná služba

Karloveská 63, P. O. Box 74, 840 00 Bratislava 4

CERTIFICATE OF ACCREDITATION

No. T-008

dated 23.11.2023

The Slovak National Accreditation Service issues a Certificate of Accreditation to an accredited body pursuant to Section 26 par.6 of Act No. 53/2023 Coll. on Accreditation of Conformity Assessment Bodies (hereinafter referred to as the "Accreditation Act").

Proficiency Testing Solutions Bulgaria Ltd.

36 Despot Slav, Smolyan, 4700, Republic of Bulgaria ID Number: 206225550

Organizational unit performing the activity of the Accredited Body: PT PROVIDER PTS Bulgaria

Workplace of the Accredited Body:

36 Despot Slav, Smolyan, 4700, Republic of Bulgaria

Identification number of the Accredited Body: 752/T-008

Area of accreditation: Proficiency testing

The proficiency testing provider demonstrated its competence to perform the accredited activity fulfilling the accreditation requirements of ISO/IEC 17043: 2010 Standard when performing organization of proficiency testing schemes in the field of testing and sampling of construction materials and constructions, and in the field of calibration of measuring instruments of dimensional quantities, calibration of measuring instruments of mechanical quantities, calibration of measuring instruments of temperature quantities, calibration of measuring instruments of physical-chemical quantities, within the accreditation scope delineated in the Annex of this Certificate of Accreditation. The Annex shall form an integral part of the Certificate of Accreditation.

Number and date of issue of the accreditation decision: No. 752/10952/2023/1 dated 23.11.2023.

Validity of the accreditation decision:

The accreditation decision No. 752/10952/2023/1 dated 23.11.2023 is valid from 23.11.2023 to 08.07.2026.

The validity of this Accreditation Certificate expires upon the expiry of the accreditation decision. the decision on withdrawal of the accreditation pursuant to Section 31 or the expiry of the accreditation pursuant to Section 32 of the Accreditation Act.

> Štefan Kr director

SNAS is signatory to the EA MLA and ILAC MRA.

The Annex is an integral part of the Certificate of Accreditation

Scope of Accreditation

Accredited body:

Proficiency Testing Solutions Bulgaria Ltd.

36 Despot Slav, Smolyan, 4700, Republic of Bulgaria

Organizational unit performing the activity of the accredited body:

PT PROVIDER PTS Bulgaria

Place of performance of the accredited body:

36 Despot Slav, Smolyan, 4700, Republic of Bulgaria

Identification number of the accredited body: 752/T-008

Specification of activities of proficiency testing provider

| Item | Field | Subject of proficiency testing | Compared properties (parameters, indicators, analytes), Range of compared values (informative) | Indication of the proficiency testing program | Other specification |
|------|--------------|-------------------------------------|--|---|-------------------------|
| | Construction | | Particle size distribution | PTS year/month-T- | |
| | | | Fines content (Percentage of fines) | XX | |
| | | | Shells content | | |
| | | | Shape index | | |
| | | | Overall flakiness index | | |
| | | | Percentage of crushed particles | | |
| | | | Percentage of totally crushed particles | | |
| | | | Percentage of totally rounded particles | | |
| | | | Polished Stone Value | - | |
| | | | Water content | | |
| | | | Loose bulk density | • | |
| | | | Particle density: | | |
| | | | - Apparent particle density | | |
| | | | - Oven- dried particle density | | |
| | | | - Saturated and surface-dried particle | | |
| | | | density | | |
| | | | - Pre-dried particle density | | At least once per years |
| | | | Water absorption | | |
| | | A | Percentage of voids | | |
| | | Aggregates | Magnesium sulfate value | | |
| . | | (lightweight and | Sand equivalent | | |
| l | | normal-weight | Methylene blue value | | |
| | | coarse, fine and all-in aggregates) | Resistance to fragmentation by static loading | | |
| | | | Resistance to fragmentation – Los Angeles coefficient | | |
| | | | Resistance to wear (micro deval | | |
| | | | coefficient) | | |
| | | | Affinity between aggregate and bitumen – | | |
| | | | degree of bitumen coverage | | |
| | | | Resistance to freezing and thawing (Loss of | | |
| | | | mass) | | |
| | | | Loss of strength of basalt aggregate | | |
| | | | Loss of mass of basalt aggregate | | |
| | | | Total content of water-soluble salts | | |
| | | | Content of water-soluble sulfates | | |
| | | | Content of acid soluble sulfates | | ANÁ AVA |
| | | | Content of lightweight contaminators | // | RODINA MARED |
| | | | Potential presence of humus | | F. 1 |
| | | | Content of water-soluble chloride salts | // 2 | 155 |
| | | | Content of acid soluble chloride salts | | [57] |
| | | | Total sulfur content | \\3 | S. Com |
| | | | 2 CHIL SMALMA COMMUNIC | // | 5 |

Annex to the Certificate of Accreditation No. T-008 dated 23.11.2023.

The Annex is an integral part of the Certificate of Accreditation

| | | T | | The second secon | te of Accreditation |
|------|--------------|---|--|--|-------------------------|
| Item | Field | Subject of proficiency testing | Compared properties (parameters, indicators, analytes), Range of compared values (informative) | Indication of the proficiency testing program | Other specification |
| | Construction | | Particle size distribution | PTS year/month-T- | |
| | | | Fines content (Percentage of fines) | XX | |
| | | | Magnesium sulfate value | + | |
| | | | Resistance to fragmentation by static loading | | |
| | | | Resistance to fragmentation – Los Angeles coefficient | | |
| | | | Shape index | 1 | |
| | | | Overall flakiness index | | |
| | | | Resistance to wear (micro deval coefficient) | - | |
| | | | Loose bulk density | | |
| | | | Percentage of voids | | |
| | | | Sand equivalent | - | |
| | | | California bearing ratio – CBR | | |
| | | | Laboratory reference density and water content - Proctor compaction: | | |
| | | | - maximum bulk density | | |
| | | | - optimum water content | | |
| | | Construction soils/ Aggregates for unbound and hydraulically bound mixtures | Percentage of crushed particles Percentage of totally crushed particles | | |
| | | | Percentage of totally rounded particles | | |
| | | | | | |
| 2 | | | | | At least once per years |
| | | | Particle density: | | |
| | | bound mixtures | - Apparent particle density | | |
| | | | - Oven- dried particle density | | |
| | | | - Saturated and surface-dried particle density | | |
| | | | - Pre-dried particle density | | |
| | | | Water absorption | | |
| | | | Plasticity Index | 1 | |
| | | | Liquid limit | | |
| | | | Plastic Limit | | |
| | | | Water content | | |
| | | | Compressive strength | | |
| | | | Particle density | | |
| | | | Elastic module, Deformation module, Deformation modules ratio | OVENSIC | |
| | | | Bulk density by substitute sand | | NARODNA AKREDI |
| | | Bulk density of skeleton b | Bulk density of skeleton by substitute sand | | 品 |
| | | | Bulk density | | 1 (25) |
| | | | | | ONTI C |

The Annex is an integral part of the Certificate of Accreditation

| Item | Field | Subject of proficiency testing | Compared properties (parameters, indicators, analytes), Range of compared values (informative) | Indication of the proficiency testing program | Other specification | | | |
|------|--------------|--------------------------------|--|---|--|--|--|--|
| | Construction | | Particle size distribution | PTS year/month-T- | | | | |
| | | | Water content | XX | | | | |
| | | | Specific density |] | | | | |
| | | | Particle density |] | | | | |
| | | | Methylene blue value | | 4 2000 | | | |
| | | | Change of softening point by delta ring and | | | | | |
| , | | Filler | ball test | | | | | |
| 3 | | riller | Total content of water-soluble salts | | | | | |
| | | | Content of water-soluble sulfates | | F-3344 | | | |
| | | | Content of acid soluble chloride salts | | | | | |
| | | | Content of acid soluble sulfates | | | | | |
| | | | Content of water-soluble chloride salts | | | | | |
| | | | Total sulfur content | | At least once per years At least once per | | | |
| | | | Penetration | PTS year/month-T- | | | | |
| | | | Softening point | XX | 1 | | | |
| | | | Elastic recovery |] | | | | |
| | | | Residual binder and oil distillate by | | | | | |
| | | | distillation | | | | | |
| | | | Properties of the residue after | | | | | |
| | | | evaporation/distillation: | | | | | |
| | | | - penetration; | | | | | |
| | | | - softening point; | | | | | |
| | | | - elastic recovery. | | | | | |
| | | | Fraass breaking point | | | | | |
| | | | Flash point | | | | | |
| | | | Solubility | | | | | |
| | | | Density | | | | | |
| | | Bitumen and | Efflux time /viscosity/ | | | | | |
| | | | Particle polarity | | | | | |
| | | | Storage stability | | | | | |
| | | | Mixing stability with cement | | | | | |
| | | | Resistance to hardening at 163°C: change | | | | | |
| | | bitumen products | of mass | | | | | |
| ١ | | (bitumen, modified bitumen, | Resistance to hardening at 163°C: retained | | | | | |
| | | emulsion, asphalt | penetration | | | | | |
| | | paste) | Resistance to hardening at 163°C: change | | | | | |
| | | paste | of softening point | | | | | |
| | | | Ductility Thermal resistance index | | | | | |
| | | | | | | | | |
| | | | Bitumen content | | | | | |
| | | | Storage stability. Penetration difference between the upper and lower layer | | | | | |
| | | | Storage stability. Softening point difference | | | | | |
| | | | between the upper and lower layer | | | | | |
| | | | Elastic recovery of the residue after loss of mass | | QODNÁ AKAR | | | |
| | | | Residue on 0,5 mm sieve | | MARY 2 | | | |
| | | | Adhesivity with limestone material | ENSK | 學 | | | |
| | | | pH | 1/3 | | | | |
| | | | 1 | ı W | ~ | | | |

Annex to the Certificate of Accreditation No. T-008 dated 23.11.2023.

The Annex is an integral part of the Certificate of Accreditation

| Item | Field | Subject of proficiency testing | Compared properties (parameters, indicators, analytes), Range of compared values (informative) | Indication of the proficiency testing program | Other specification |
|--------|--------------|--------------------------------|--|---|--|
| | Construction | | Maximum density | PTS year/month-T- | |
| | | | Air voids content | XX | |
| | | | Bulk density | | |
| | | | Stability | | |
| | | | Flow | | |
| | | | Particle size distribution | | |
| | | Asphalt | Soluble binder content | | At least once per 5 years |
| 5 | | (bitumineous) | Indirect tensile strength | | |
| | | mixtures | Indirect tensile strength ratio (Water | | |
| | | | sensitivity) | | |
| | | | Binder drainage | | |
| | | | Dimensions of a bituminous specimen" | | |
| | | | -height; | | |
| | | | | | |
| | | | - diameter; | | ar/month-T- XX At least once per years At least once per years ar/month-T- XX At least once per years |
| | | Laid and | Immanularity of novement coveres /the | DTC voor/month T | |
| , | | | Irregularity of pavement courses /the | | At least once per 5 |
| 6 | | compacted | straightedge test/ | | years |
| | | bituminous layers | Thickness of a bituminous pavement | DOG / 1 TO | • |
| | | | Air content | PTS year/month-T- | |
| | | | Slump | XX | At least once per 5 |
| 7 | | Fresh concrete | Density | | • |
| | | | Flow table test | | years |
| | | | Communication | DTC/ | |
| | | | Compressive strength | PTS year/month-T- | At least once per 5 |
| | | | Freeze-thaw resistance with de-icing salts | | |
| | | | Density | | |
| | | | Tensile splitting strength | | |
| | | | Flexural strength | | |
| 8 | | Hardened concrete | Water impermeability / Depth of | | - |
| | | | penetration of water under pressure | | years |
| | | | Rebound number | | |
| | | | Resistance to direct freezing and thawing - | | |
| | | | loss of mass; | | |
| | | | -loss of compressive strength | | |
| | | | Compressive strength | PTS year/month-T- | At least once per 5 |
| | | | Setting times | | 7.5 |
| _ | | Q 4 | Soundness | | , |
| 9 | | Cement | Standard consistence | 1 | |
| | | | Standard Consistence | - | |
| | | | | DEG / 1 E | |
| | | Sprayed concrete | Energy absorption capacity | PTS year/month-T- | - |
| 0 | | | Compressive strength of young sprayed | XX | years |
| | | | concrete | | |
| | | 1/ | Dulle donaity of fire-hamanta | DTC ween/month T | At loost one 5 |
| | | Mortars | Bulk density of fresh mortar | PTS year/month-T- | _ |
| | | (Construction | Particle size distribution | _ ^^ | years |
| | | mortars and construction | Dry bulk density of hardened mortar | | |
| 1 | | | Flexural strength | | |
| | | mortars for screed | Compressive strength | _ | |
| | 1 | materials) | Adhesive strength on substrates | | GODNA AKAR |
| | | | | | 2 0/4 |
| \neg | | Grout for | Fluidity | PTS year/month-T- | At least once per 5 |
| | | prestressing | Truidity | | years o |
| 12 | | tendons | | XX 🙀 | WW E |
| . 2 | 1 | tendons | Compressive strength | 31 (3 | |

The Annex is an integral part of the Certificate of Accreditation

| Certificate of Accredit | | | | | |
|-------------------------|---|--|--|---|--|
| Item | Field | Subject of proficiency testing | Compared properties (parameters, indicators, analytes), Range of compared values (informative) | Indication of the proficiency testing program | Other specification |
| | Construction | | Tensile splitting strength | PTS year/month-T- | At least once per 5 |
| | | proficiency testing | Water absorption | XX | years |
| | | | Resistance to frost (Loss of mass after test | | |
| | | | freeze – thaw with de-icing salt) | | |
| 10 | | | Failure load | _ | |
| 13 | | | Shape and dimensions | _ | |
| | | Concrete paving | Bending strength | | |
| | | | Abrasive wear (abrasion according to the Böhme test) | | |
| | | | Thickness of cover layer | - | |
| | | | Unpolished slip resistance | - | |
| | | Masonry units | Geometric dimensions and shape | PTS year/month-T- | At least once per 5 |
| | | mason y anno | Water absorption | XX | years |
| | | | - water absorption coefficient due to | | Jeans |
| | | | capillary | | |
| 1.4 | | | - initial rate of water absorption | | |
| 14 | | | Compressive strength | 1 | |
| | | | Water absorption | | |
| | | | Dry density: | | |
| | | | - gross density | | |
| | | | - net density | | |
| | | | Bond strength | PTS year/month-T- | At least once per 5 |
| | | | | XX | years |
| 15 | | | | | |
| | | | | | |
| | | | | | |
| | | · cmcics | Lightweight aggregates | | |
| | | | Aggregates | | |
| | | | Fine aggregates | | |
| | | | All-in aggregates | | |
| | | | Construction soils | PTS year/month-S-XX At least once years | |
| | | | Aggregates for unbound and hydraulically | | |
| | | | bound mixtures | | |
| | | | Filler | | |
| | | Sampling of | Bitumen | | At least once per 5 |
| 16 | | | Modified bitumen | | |
| | | | Emulsion | | y curs |
| | | | Asphalt paste | | |
| | | | Asphalt (bituminous) mixtures Laid and compacted asphalt (bituminous) | | |
| | | | mixtures | | |
| | | | Fresh concrete | | |
| | | | Cement | | |
| | | | Sprayed concrete | | |
| | | | Construction mortars | | |
| | | | Construction mortars for screed materials | | |
| | Length and | | Micrometers | PTS year/month-C- | At least once per 5 years ROONA AKREONA |
| | Plane angle Calibration of measuring instruments for | | Caliper devices | XX | |
| | | 1200 100000-1000-1000-1000-000-000-000-000 | Line scales and measuring tapes | | |
| ,, | | | Measuring microscopes and profile | | |
| 17 | | 1-Manage Cold (September 1) Statement Action (September 1) | projectors | | |
| | | geometrical | Dial gauges | NS. | |
| | | quantities | Gauges blocks and measurement Standards | \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\ | (E |
| | | | Plain angle gauges | 1 2 | 20/ |
| | | | | # | SNAS |

Annex to the Certificate of Accreditation No. T-008 dated 23.11.2023.

The Annex is an integral part of the Certificate of Accreditation

| | Certificate of Accreatituti | | | | |
|------|-----------------------------|--------------------------------|--|---|------------------------|
| Item | Field | Subject of proficiency testing | Compared properties (parameters, indicators, analytes), Range of compared values (informative) | Indication of the proficiency testing program | Other specification |
| | Force and | | Force gauges | PTS year/month-C- | At least once per 5 |
| 18 | moment of | | Force testing machines | XX | years |
| 10 | force meters | Calibration of | Hardness blocks and testers | | |
| | | measuring | Torque measuring instruments | | |
| 19 | Pressure | instruments of | Pressure measuring instruments | PTS year/month-C- | At least once per 5 |
| 19 | | mechanical | | XX | years |
| | Mass | quantities | Balances/scales | PTS year/month-C- | At least once per 5 |
| 20 | | | Weights | XX | years |
| | | | Volume measures by gravimetric method | | |
| | Temperature | Calibration of | Temperature indicators and simulators | PTS year/month-C- | At least once per 5 |
| | | measuring | Temperature transducers and sensors | XX | years |
| 21 | | instruments of | | | |
| | | temperature | Thermometers | | |
| | | quantities | | | 3 6 |
| | Physico- | Calibration of | pH Meters | PTS year/month-C- | At least once per 5 |
| | chemical | measuring | Conductometers | XX | years |
| 22 | quantities | instruments of | Spectrophotometers | | |
| | | physicochemical quantities | Hygrometers for relative humidity of air | | |

